

SIGANMETRIC

UHF LONG RANGE READERS

SIGAN SR68M

6~8M UHF RFID READER

RFID
identification
and
recognition
systems
medium & long



Frequency
865-868MHz(EU),
902-928MHz(US)



Operation mode
Active, trigger, answer, password
mode(optional)



Reading range
7dbi antenna with effect distance up
to 6-8M ideally



Weather rating
IP 66, RH 90%,
Temperature -20°C~60°C



Supported tags
ISO18000-6B, ISO18000-6C(EPC C1G2)



Bracket type
Wall mount, Column type



Interface
RS232,USB, WG26, Relay,TCP/IP,
PoE, WiFi



Power supply
9-36VDC, 1.0A Consumption
20Watt(max)



RF Transmission power
26dbm(adjustable)



Dimensions (mm)
260(W) x 260(H) x 70(T)

Illustration



Applications

Parking access control
Tool tracking ,
IT asset tracking,
Race timing,
Laundry management,
etc.

ordering nomenclature

SIGAN SR68 MR	6-8M UHF RFID Reader with RS232, USB, WG26, Relay(9V power)
SIGAN SR68 MRT	6-8M UHF RFID Reader with RS232, USB, WG26, Relay TCP/IP, POE
SIGAN SR68 MRTW	6-8M UHF RFID Reader with RS343, USB, WG26, Relay, TCP/IP, POE, WIFI

sales@siganmetric.com

SIGANMETRIC
UHF long range readers



www.sigametric.com